

AUTOMAX SULFUR IN-ACTIVE TRI PURPOSE METAL-WORKING OILS

AUTOMAX METAL-WORKING OILS are multi-purpose, light colored cutting fluids of the non-staining type. They are specifically designed for use in the machining of non-ferrous metals where the use of "active sulfur" containing cutting oils result in the staining of non-ferrous parts and machine-tool components.

AUTOMAX METAL-WORKING OILS are designed for use as both a cutting oil and a machine tool lubricant. These oils are effective in reducing friction on the part / tool interface while remaining inactive (non-corrosive) in the machine tool lubrication system under conditions normally encountered.

The in-active (non-corrosive) feature of these oils makes them well suited for the machining of copper and its alloys as well as a variety of operations on ferrous metals where machinability requirements range from mild to moderately severe. **AUTOMAX METAL-WORKING OILS** also contain additives to control misting.

A blend of paraffinic base stocks are incorporated into the **AUTOMAX OILS** along with a combination of extreme pressure sulfurized polyolefins and friction-modifying compounds to promote optimum performance while exhibiting improved environmental conditions for operators such as lower mist as well as improved thermal stability and smoking tendencies. They also have very low pour points to facilitate handling at lower temperatures. **AUTOMAX OILS** are not formulated with chlorine or chlorinated paraffins.

The use of **AUTOMAX METAL-WORKING OILS** in multi-spindle automatic screw machines, as both cutting oil and lube oil, is most effective where dilution of the cutting fluid by the oil from a leaking lube oil system is encountered. Dual / Tri- purpose oils are not intended for use in hydraulic systems with pumps and pressures and speeds requiring the use of an anti-wear type hydraulic oil.

Typical Physical and Chemical Properties

AUTOMAX	177	20	22	25	38	40	45	50
Item Number	04068	04070	04322	04325	04338	04340	04345	04350
Appearance	Straw	Straw	Straw	Straw	Straw	Straw	Straw	Straw
Flash Point, COC F	>275	>350	>350	>350	>350	>350	>350	>350
Specific Gravity, 60 F	.88	.88	.87	.87	.87	.87	.87	.88
Viscosity, SUS @ 100 F	85	105	135	120	160	145	170	200
Sulfur, % Total	0.65	1.5	1.0	.75	1.0	2.0	1.5	2.0
Sulfur, % Active	nil	nil	nil	nil	nil	nil	nil	nil
Chlorine, %	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-
Fatty Olefin / Oil-Film Components, %	3.5	8.0	5.5	4.0	5.5	12	8.0	12

AUTOMAX METAL-WORKING OILS are available in 55 gallon steel drums, totes and bulk quantities.

AUTOMAX METAL-WORKING OILS CONTINUED:

Shipping Identification / labeling:

D.O.T. ID.: PETROLEUM PRODUCTS,
CLASS 65 NMFC155250
(NOT D.O.T. REGULATED)

HMIS	
Health	1
Flammability	1
Reactivity	0
Personal Protection	⌘

Per OSHA Std. 29 CFR 1910.1200: Read and understand the Material Safety Data Sheet before handling or disposing of this material.

DISCLAIMER Information contained herein is believed to be correct and reliable. However, Maxim Petrochemical Corporation does not assume liability for it or for recommendations of our representatives inasmuch as conditions and methods of use are beyond our control. Further, we make no warranty, expressed or implied, of any kind regarding those products or their use and purchaser assumes all risks of use or handling either in accordance with directions or not.

MANUFACTURER DISCLAIMER The information and recommendations contained herein are, to the best of the knowledge and belief of Maxim Petrochemical Corporation, accurate and reliable as of the date issued. Maxim does not warrant or guarantee their reliability, and Maxim shall not be liable for any loss or damage arising out of use thereof. The information and recommendations are for the user's consideration and examination. Conditions of use are beyond Maxim's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling, and disposal of the product(s). This information relates only to the product(s) designated herein and does not relate to its use in combination with any other material or in any other process

**For additional information, product samples, etc., please contact;
MAXIM OIL & CHEMICAL COMPANY
Fort Worth, Texas, 76140 - (817) 654-4456
www.maximoil.com**

Rev:3.1-11/12ln